

# Semi Integrated - Kronos TL

## Technical Data



	230 TL		234 TL		261 TL		265 TL		266 TL		267 TL		268 TL		274 TL		282 TL	
<b>MECHANICAL UNIT / CHASSIS</b>																		
Mechanical unit	Ford Transit	Fiat Ducato	Ford Transit	Fiat Ducato	Ford Transit	Fiat Ducato	Ford Transit	Fiat Ducato	Ford Transit	Fiat Ducato	Ford Transit	Fiat Ducato	Ford Transit	Fiat Ducato	Ford Transit	Fiat Ducato	Ford Transit	Fiat Ducato
Engine	2.0 TDI 130 CV	2.3 MJ 120 CV	2.0 TDI 130 CV	2.3 MJ 120 CV	2.0 TDI 130 CV	2.3 MJ 120 CV	2.0 TDI 130 CV	2.3 MJ 120 CV	2.0 TDI 130 CV	2.3 MJ 120 CV	2.0 TDI 130 CV	2.3 MJ 120 CV	2.0 TDI 130 CV	2.3 MJ 120 CV	2.0 TDI 130 CV	2.3 MJ 120 CV	2.0 TDI 130 CV	2.3 MJ 120 CV
Max. allowed weight (Kg)	3500	3500	3500	3500	3500	3500	3500	3500	3500	3500	3500	3500	3500	3500	3500	3500	3500	3500
Weight in running order (Min / Max Kg)	2935 / 3169	2898 / 3169	3015 / 3115	2980 / 3080	2965 / 3162	2928 / 3162	3015 / 3072	2978 / 3072	3115 / 3157	3150 / 3160	3025 / 3157	2988 / 3157	3055 / 3157	3018 / 3157	2945 / 2988	2923 / 2988	3015 / 3072	3008 / 3072
Payload (Min / Max Kg)	331 / 565	331 / 602	485 / 385	520 / 420	338 / 535	338 / 572	428 / 485	428 / 522	385 / 343	350 / 340	343 / 475	343 / 512	343 / 445	343 / 482	512 / 555	512 / 577	428 / 485	428 / 492
Wheelbase (mm)	3954	4035	3750	3800	3750	3800	3954	4035	3954	4035	3954	4035	3954	4035	3954	4035	3954	3800
Motorhome weight plus trailer (kg)	5065	5500	5065	5500	5065	5500	5065	5500	5065	5500	5065	5500	5065	5500	5065	5500	5065	5500
Wheels dimensions	16"	15"	16"	15"	16"	15"	16"	15"	16"	15"	16"	15"	16"	15"	16"	15"	16"	15"
<b>DIMENSIONS AND PLACES</b>																		
External length (mm) / External width (mm)	6200 / 2350		6990 / 2350		6990 / 2350		7450 / 2350		7450 / 2350		7450 / 2350		7430 / 2350		7330 / 2350		7430 / 2350	
External height (mm) / Internal height (mm)	2950 / 2080		2950 / 2080		2950 / 2080		2950 / 2080		2950 / 2080		2950 / 2080		2950 / 2080		2950 / 2080		2950 / 2080	
Approved seats	4		4		4		4		4		4		4		6		5	
Beds (optional dinette)	4		4		4 (5 0)		4 (5 0)		4 (5 0)		4 (5 0)		4		6		4 (5 0)	
Extra bed from the convertible dinette	S		S		0		0		0		0		S		S		0	
Rear bed (cm)	210x70		210x70		190x150		190x150		190x150		190x150		190x150		216x100(84) / 216x100(84)		204x80 / 193x80	
Additional auxiliary bed in dinette (cm)	216x77		216x125		216x90(80)		212x54		216x101		212x100		-		200x62 / 189x65		212x50	
Overcab bed (cm) / Elevating Bed (cm)	- / 190 x 148(123)		- / 190x160		- / 190x116(95)		- / 190x128(107)		- / 190x128(107)		- / 190x128(107)		- / 190x128(107)		- / 190x133(124)		- / 190x128(107)	
Additional rear bed seat	-		-		-		-		-		-		-		S		0	
Sliding bed system	-		-		S		S		S		S		-		-		-	
Locker (useful opening, cm)	147x67 / 100x67		147x67 / 100x67		117x 87(72) / 72x87(72)		117x87(72) / 72x87(72)		117x87(72) / 72x87(72)		117x 87(72) / 72x87(72)		117x87x(72) / 40x87(72)		100x67 / 100x67		42x97 - 60x52 - 42x97	
Max. internal garage height (mm)	130		130		128		128		128		128		120		138		77	
Floor / walls / roof thickness (mm)	54 / 31 / 31		54 / 31 / 31		54 / 31 / 31		54 / 31 / 31		54 / 31 / 31		54 / 31 / 31		54 / 31 / 31		54 / 31 / 31		54 / 31 / 31	
Floor / walls / roof material (mm)	VTR / VTR / VTR		VTR / VTR / VTR		VTR / VTR / VTR		VTR / VTR / VTR		VTR / VTR / VTR		VTR / VTR / VTR		VTR / VTR / VTR		VTR / VTR / VTR		VTR / VTR / VTR	
Fiberglass roof, hail-proof	S		S		S		S		S		S		S		S		S	
<b>INSTALLATIONS</b>																		
Burners / Gas oven / Suction hood	3 / 0 / -		3 / 0 / -		3 / 0 / -		3 / 0 / -		2 / 0 / -		3 / 0 / -		3 / 0 / -		3 / 0 / -		3 / 0 / -	
Tank capacity: clear water / wastewater (L**)	(20)100 / 120 (20)100 / 100		(20)100 / 120 (20)100 / 100		(20)100 / 120 (20)100 / 100		(20)100 / 120 (20)100 / 100		(20)100 / 120 (20)100 / 100		(20)100 / 120 (20)100 / 100		(20)100 / 120 (20)100 / 100		(20)100 / 120 (20)100 / 100		(20)100 / 120 (20)100 / 100	
Automatic trivalent fridge (220V, 12V, gas) (L)	140		140		140		140		140		140		90		140		140	
Standard heating system	Gas Combi 4000 W		Gas Combi 4000 W		Gas Combi 4000 W		Gas Combi 4000 W		Gas Combi 4000 W		Gas Combi 4000 W		Gas Combi 4000 W		Gas Combi 4000 W		Gas Combi 4000 W	
<b>SKYLIGHTS</b>																		
Panoramic Roof (mm)	S (1000x800)		S (1000x800)		S (1000x800)		S (1000x800)		S (1000x800)		S (1000x800)		S (1000x800)		S (1000x800)		S (1000x800)	
Rear window (mm)	400x400		400x400		400x400 ( 0 700x500)		400x400 ( 0 700x500 )		400x400 ( 0 700x500 )		400x400 ( 0 700x500 )		400x400 ( 0 700x500 )		400x400 ( 0 700x500 )		400x400 ( 0 700x500 )	
Central skylight (mm)	400x400 ( 0 700x500 )		400x400 ( 0 700x500 )		400x400		400x400		400x400		400x400		400x400		400x400		400x400	
Skylight dinette	-		-		-		-		-		-		-		-		-	
Skylight toilette/shower	- / S		- / S		- / S		- / S		- / S		- / S		- / S		S		S	
<b>STANDARD EQUIPMENT</b>																		
Painted front bumper	S		S		S		S		S		S		S		S		S	
16 " wheels (FORD)	S		S		S		S		S		S		S		S		S	
Solar Panel	S		S		S		S		S		S		S		S		S	
Rear camera	S		S		S		S		S		S		S		S		S	
Entrance door with fixed window	S		S		S		S		S		S		S		S		S	
Flyscreen for entrance door	S		S		S		S		S		S		S		S		S	
ESC (FIAT) ESP (FORD)	S		S		S		S		S		S		S		S		S	
Integrated DAB radio antenna & bluetooth radio with steering wheel controls (FORD)	S		S		S		S		S		S		S		S		S	
Manual air conditioning	S		S		S		S		S		S		S		S		S	
Driver and Passenger airbag	S		S		S		S		S		S		S		S		S	
Cruise Control with speed limiter	S		S		S		S		S		S		S		S		S	
Swivelling driver' and passenger's seat	S		S		S		S		S		S		S		S		S	
Beds with staves	S		S		S		S		S		S		S		S		S	

The mass of the approved vehicle includes: driver (75 Kg), diesel tank filled to 100% (60 liters), fresh water filled to 20 liters. (use of the special exhaust valve) and aluminum gas cylinders (max. 15 kg.) full to 90% of their capacity, and tolerance foreseen in the approval phase (+/- 5%) (2007/46 / EC). Anything not included in the standard version of the vehicle, both airframe and chassis, leads to an increase in the curb weight with the consequent reduction of the payload up to the possible reduction of homologated seats in case the total weight is the value of the available payload . The available payloads result from the difference between the maximum permissible mass and the mass in running order and have a tolerance of 5%. During the purchase phase, it is necessary to check the weight of the options to be installed on the vehicle.

S= standard O=optional - = unavailable VTR= Fiberglass