

Livingstone Advance - Van Technical Data



	LIVINGSTONE ADVANCE K2	LIVINGSTONE ADVANCE 2	LIVINGSTONE ADVANCE 4	LIVINGSTONE ADVANCE 5	LIVINGSTONE ADVANCE 6	LIVINGSTONE ADVANCE DUO	LIVINGSTONE ADVANCE DUO XL
MECHANICAL UNIT / CHASSIS							
Mechanical unit	Fiat Ducato	Fiat Ducato	Fiat Ducato	Fiat Ducato	Fiat Ducato	Fiat Ducato	Fiat Ducato
Engine	2.3 MJ 120 CV	2.3 MJ 120 CV	2.3 MJ 120 CV	2.3 MJ 120 CV	2.3 MJ 120 CV	2.3 MJ 120 CV	2.3 MJ 120 CV
Max. allowed weight (Kg)	3300	3300	3300	3300	3300	3300	3500
Weight in running order (Min / Max Kg)	2663 / 2883	2753 / 2933	2803 / 2963	2773 / 2953	2833 / 2972	2903 / 3143	2903 / 3143
Payload (Min / Max Kg)	417 / 637	367 / 547	337 / 497	347 / 497	327 / 527	357 / 597	357 / 597
Wheelbase (mm)	3450	4035	4035	4035	4035	4035	4035
Maximum towable weight (kg)	2500	2500	2500	2500	2500	2500	2500
Wheels dimensions	16"	16"	16"	16"	16"	16"	16"
DIMENSIONS AND PLACES							
External length (mm) / External width (mm)	5410 / 2050	5995 / 2050	5995 / 2050	5995 / 2050	5995 / 2050	6365 / 2050	6365 / 2050
External height (mm) / Internal height (mm)	2650 / 1890	2650 / 1890	2650 / 1890	2650 / 1890	2650 / 1890	2650 / 1890	2650 / 1890
Approved seats	4	4	4	4	4	4	4
Beds	2	2 + 1	2 + 1	4 + 1	2 + 1	2 + 1	2 + 1
Rear bed (cm)	190x133	190x144	190x144	190x144 - 186x132	174x75 - 190x62	195x80 - 190x80	-
Drop-down rear bed (cm)	-	-	-	-	-	-	190/180x192
Bed in Dinette (cm)	140x45	180x97	180x97	180x97	175x90	150x50	150x50
INSTALLATIONS							
Burners	2	2	2	2	2	2	2
Tank capacity: clear water / wastewater (L**)	90 / 90	100 / 90	100 / 90	100 / 90	100 / 90	100 / 90	100 / 90
Trivalent fridge (220V, 12V, gas) (L)	-	80	140	80	-	80	-
Compressor fridge (L)	70	-	-	-	70	-	90
Standard heating system	4000Kw DIESEL	4000Kw DIESEL	4000Kw DIESEL	4000Kw DIESEL	4000Kw DIESEL	4000Kw DIESEL	4000Kw DIESEL
Internal insulation material	POLYESTER FIBER AND ALUMINUM FILM	POLYESTER FIBER AND ALUMINUM FILM	POLYESTER FIBER AND ALUMINUM FILM	POLYESTER FIBER AND ALUMINUM FILM	POLYESTER FIBER AND ALUMINUM FILM	POLYESTER FIBER AND ALUMINUM FILM	POLYESTER FIBER AND ALUMINUM FILM
Floor thickness (mm)	30	30	30	30	30	30	30
SKYLIGHTS							
Skylight 400x400 mm	1	1	1	1	1	1	1
STANDARD EQUIPMENT							
ESC	S	S	S	S	S	S	S
16 '' alloy wheels	S	S	S	S	S	S	S
Integrated DAB radio antenna	S	S	S	S	S	S	S
Swivelling cab seats with covers coordinated with the upholstery	S	S	S	S	S	S	S
Manual air conditioning	S	S	S	S	S	S	S
Cruise Control	S	S	S	S	S	S	S
Pleated cab blind	S	S	S	S	S	S	S
Electric mirrors	S	S	S	S	S	S	S
Driver and Passenger airbag	S	S	S	S	S	S	S
Mosquito net	S	S	S	S	S	S	S
Electric step	S	S	S	S	S	S	S
6 years infiltration guarantee	S	S	S	S	S	S	S

The mass of the approved vehicle includes: driver (75 Kg), diesel tank filled to 100% (60 liters), fresh water filled to 20 liters, (use of the special exhaust valve) and aluminum gas cylinders (max. 15 kg.) full to 90% of their capacity, and tolerance foreseen in the approval phase (+/- 5%) (2007/46 / EC). Anything not included in the standard version of the vehicle, both airframe and chassis, leads to an increase in the curb weight with the consequent reduction of the payload up to the possible reduction of homologated seats in case the total weight is the value of the available payload . The available payloads result from the difference between the maximum permissible mass and the mass in running order and have a tolerance of 5%. During the purchase phase, it is necessary to check the weight of the options to be installed on the vehicle.

S= standard O=optional - = unavailable

** = The vehicle in running order must have the fresh water tank filled to 20 liters, using the special drain cock supplied.