

Integrated Motorhomes - Zefiro

Technical Data



	265 Integral	267 Integral	274 Integral	284 Integral	287 Integral
MECHANICAL UNIT / CHASSIS					
Mechanical unit	Fiat Ducato	Fiat Ducato	Fiat Ducato	Fiat Ducato	Fiat Ducato
Engine	2.3 MJ 120 CV	2.3 MJ 120 CV	2.3 MJ 120 CV	2.3 MJ 120 CV	2.3 MJ 120 CV
Max. allowed weight (Kg)	3500	3500	3500	3500	3500
Weight in running order (Min / Max Kg)	2968 / 3072	2978 / 3157	2923 / 2988	2968 / 3072	2978 / 3157
Payload (Min / Max Kg)	428 / 532	343 / 532	512 / 577	428 / 532	343 / 522
Wheelbase (mm)	4035	4035	4035	4035	4035
Motorhome weight plus trailer (kg)	5500	5500	5500	5500	5500
Wheels dimensions	15"	15"	15"	15"	15"
DIMENSIONS AND PLACES					
External length (mm) / External width (mm)	7450 / 2350	7450 / 2350	7300 / 2350	7450 / 2350	6970 / 2350
External height (mm) / Internal height (mm)	2950 / 2080	2950 / 2080	2950 / 2080	2950 / 2080	2950 / 2080
Approved seats	5	4	6	5	4
Beds (optional dinette)	4 (5 0)	4 (5 0)	6	4 (0 5)	4 (5 0)
Extra bed from the convertible dinette	0	0	-	0	0
Rear bed (cm)	190x150	190x150	216x100(840) – 216x100(840)	220x80 – 194x80	200x80 – 215x80
Additional auxiliary bed in dinette (cm)	212x54	212x100	200x62 – 189x65	212x54	212x100
Overcab bed (cm) / Elevating Bed (cm)	- / 185x134	- / 185x134	- / 185x134	- / 185x134	- / 185x134
Additional rear bed seat	-	-	-	-	S
Sliding bed system	-	-	-	-	-
Locker (useful opening, cm)	117x87(72) / 72x87(72)	117x 87(72) / 72x87(72)	100x67 / 100x67	117x87(72) / 117x87(72)	117x87(72) / 117x87(72)
Max. internal garage height (mm)	128	128	138	119	120
Floor / walls / roof thickness (mm)	54 / 31 / 31	54 / 31 / 31	54 / 31 / 31	54 / 31 / 31	54 / 31 / 31
Floor / walls / roof material (mm)	VTR / VTR / VTR	VTR / VTR / VTR	VTR / VTR / VTR	VTR / VTR / VTR	VTR / VTR / VTR
Fiberglass roof, hail-proof	S	S	S	S	S
INSTALLATIONS					
Burners / Gas oven / Suction hood	3 / 0 / -	3 / 0 / -	3 / 0 / -	3 / 0 / -	3 / 0 / -
Tank capacity: clear water / wastewater (L**)	(20)100 / 100	(20)100 / 100	(20)100 / 100	(20)100 / 100	(20)100 / 100
Automatic trivalent fridge (220V, 12V, gas) (L)	140	140	140	140	140
Standard heating system	Gas Combi 4000 W	Gas Combi 4000 W	Gas Combi 4000 W	Gas Combi 4000 W	Gas Combi 4000 W
SKYLIGHTS					
Panoramic Roof (mm)	-	-	-	-	-
Rear window (mm)	400x400 (0 700x500)	400x400 (0 700x500)	400x400 (0 700x500)	400x400 (0 700x500)	400x400 (0 700x500)
Central skylight (mm)	400x400	-	400x400	700x500 (0 HEKI 3 960x655)	-
Skylight dinette	-	700x500 (0 HEKI 3 960x655)	-	-	700x500 (0 HEKI 3 960x655)
Skylight toilette/shower	- / S	- / S	- / S	- / S	- / S
STANDARD EQUIPMENT					
Solar Panel	S	S	S	S	S
Double rear camera with parking function	S	S	S	S	S
Entrance door with fixed window	S	S	S	S	S
Pleated cab blind	S	S	S	S	S
Flyscreen for entrance door	S	S	S	S	S
ESC (FIAT)	S	S	S	S	S
Strip opening with locker	S	S	S	S	S
Integrated DAB radio antenna & 2 DIN radio with Carplay	S	S	S	S	S
Manual air conditioning	S	S	S	S	S
Driver and Passenger airbag	S	S	S	S	S
Cruise Control with speed limiter	S	S	S	S	S
Swivelling driver' and passenger's seat	S	S	S	S	S
Beds with staves	S	S	S	S	S

The mass of the approved vehicle includes: driver (75 Kg), diesel tank filled to 100% (60 liters), fresh water filled to 20 liters. (use of the special exhaust valve) and aluminum gas cylinders (max. 15 kg.) full to 90% of their capacity, and tolerance foreseen in the approval phase (+/- 5%) (2007/46 / EC). Anything not included in the standard version of the vehicle, both airframe and chassis, leads to an increase in the curb weight with the consequent reduction of the payload up to the possible reduction of homologated seats in case the total weight is the value of the available payload . The available payloads result from the difference between the maximum permissible mass and the mass in running order and have a tolerance of 5%. During the purchase phase, it is necessary to check the weight of the options to be installed on the vehicle.

S= standard O=optional - = unavailable VTR= Fiberglass