

Semi Integrated - Zefiro TL

Technical Data



	230 TL	234 TL	261 TL	265 TL	266 TL	267 TL	268 TL	274 TL	282 TL
MECHANICAL UNIT / CHASSIS									
Mechanical unit	Fiat Ducato	Fiat Ducato	Fiat Ducato	Fiat Ducato	Fiat Ducato	Fiat Ducato	Fiat Ducato	Fiat Ducato	Fiat Ducato
Engine	2.3 MJ 120 CV	2.3 MJ 120 CV	2.3 MJ 120 CV	2.3 MJ 120 CV	2.3 MJ 120 CV	2.3 MJ 120 CV	2.3 MJ 120 CV	2.3 MJ 120 CV	2.3 MJ 120 CV
Max. allowed weight (Kg)	3500	3500	3500	3500	3500	3500	3500	3500	3500
Weight in running order (Min / Max Kg)	2898 / 3169	2980 / 3080	2928 / 3162	2978 / 3072	3150 / 3160	2988 / 3157	3018 / 3157	2923 / 2988	3008 / 3072
Payload (Min / Max Kg)	331 / 602	520 / 420	338 / 572	428 / 522	350 / 340	343 / 512	343 / 482	512 / 577	428 / 492
Wheelbase (mm)	4035	4035	3800	4035	4035	4035	4035	4035	3800
Motorhome weight plus trailer (kg)	5500	5500	5500	5500	5500	5500	5500	5500	5500
Wheels dimensions	15"	15"	15"	15"	15"	15"	15"	15"	15"
DIMENSIONS AND PLACES									
External length (mm) / External width (mm)	6200 / 2350	6990 / 2350	6990 / 2350	7450 / 2350	7450 / 2350	7450 / 2350	7430 / 2350	7330 / 2350	7430 / 2350
External height (mm) / Internal height (mm)	2950 / 2080	2950 / 2080	2950 / 2080	2950 / 2080	2950 / 2080	2950 / 2080	2950 / 2080	2950 / 2080	2950 / 2080
Approved seats	4	4	4	4	4	4	4	6	5
Beds (optional dinette)	4	4	4 (5 0)	4 (5 0)	4 (5 0)	4 (5 0)	4	6	4 (5 0)
Extra bed from the convertible dinette	S	S	0	0	0	0	S	S	0
Rear bed (cm)	210x70	210x70	190x150	190x150	190x150	190x150	190x150	216x100(84) / 216x100(84)	204x80 / 193x80
Additional auxiliary bed in dinette (cm)	216x77	216x125	216x90(80)	212x54	216x101	212x100	-	200x62 / 189x65	212x50
Overcab bed (cm) / Elevating Bed (cm)	- / 190 x 148(123)	- / 190x160	- / 190x116(95)	- / 190x128(107)	- / 190x128(107)	- / 190x128(107)	- / 190x128(107)	- / 190x133(124)	- / 190x128(107)
Additional rear bed seat	-	-	-	-	-	-	-	S	0
Sliding bed system	-	-	S	S	S	S	-	-	-
Locker (useful opening, cm)	147x67 / 100x67	147x67 / 100x67	117x 87(72) / 72x87(72)	117x87(72) / 72x87(72)	117x87(72) / 72x87(72)	117x87(72) / 72x87(72)	117x87x(72) / 40x87(72)	100x67 / 100x67	42x97 - 60x52 - 42x97
Max. internal garage height (mm)	130	130	128	128	128	128	120	138	77
Floor / walls / roof thickness (mm)	54 / 31 / 31	54 / 31 / 31	54 / 31 / 31	54 / 31 / 31	54 / 31 / 31	54 / 31 / 31	54 / 31 / 31	54 / 31 / 31	54 / 31 / 31
Floor / walls / roof material (mm)	VTR / VTR / VTR	VTR / VTR / VTR	VTR / VTR / VTR	VTR / VTR / VTR	VTR / VTR / VTR	VTR / VTR / VTR	VTR / VTR / VTR	VTR / VTR / VTR	VTR / VTR / VTR
Fiberglass roof, hail-proof	S	S	S	S	S	S	S	S	S
INSTALLATIONS									
Burners / Gas oven / Suction hood	3 / 0 / -	3 / 0 / -	3 / 0 / -	3 / 0 / -	2 / 0 / -	3 / 0 / -	3 / 0 / -	3 / 0 / -	3 / 0 / -
Tank capacity: clear water / wastewater (L**)	(20)100 / 120 (20)100 / 100	(20)100 / 120 (20)100 / 100	(20)100 / 120 (20)100 / 100	(20)100 / 120 (20)100 / 100	(20)100 / 120 (20)100 / 100	(20)100 / 120 (20)100 / 100	(20)100 / 120 (20)100 / 100	(20)100 / 120 (20)100 / 100	(20)100 / 120 (20)100 / 100
Automatic trivalent fridge (220V, 12V, gas) (L)	140	140	140	140	140	140	90	140	140
Standard heating system	Gas Combi 4000 W	Gas Combi 4000 W	Gas Combi 4000 W	Gas Combi 4000 W	Gas Combi 4000 W	Gas Combi 4000 W	Gas Combi 4000 W	Gas Combi 4000 W	Gas Combi 4000 W
SKYLIGHTS									
Panoramic Roof (mm)	S (1000x800)	S (1000x800)	S (1000x800)	S (1000x800)	S (1000x800)	S (1000x800)	S (1000x800)	S (1000x800)	S (1000x800)
Rear window (mm)	400x400	400x400	400x400 (0 700x500)	400x400 (0 700x500)	400x400 (0 700x500)	400x400 (0 700x500)	400x400 (0 700x500)	400x400 (0 700x500)	400x400 (0 700x500)
Central skylight (mm)	400x400 (0 700x500)	400x400 (0 700x500)	400x400	400x400	400x400	400x400	400x400	400x400	400x400
Skylight dinette	-	-	-	-	-	-	-	-	-
Skylight toilette/shower	- / S	- / S	- / S	- / S	- / S	- / S	- / S	- / S	- / S
STANDARD EQUIPMENT									
Painted front bumper	S	S	S	S	S	S	S	S	S
Solar Panel	S	S	S	S	S	S	S	S	S
Double rear camera with parking function	S	S	S	S	S	S	S	S	S
Entrance door with fixed window	S	S	S	S	S	S	S	S	S
Flyscreen for entrance door	S	S	S	S	S	S	S	S	S
Strip opening with locker	S	S	S	S	S	S	S	S	S
ESC (FIAT)	S	S	S	S	S	S	S	S	S
Integrated DAB radio antenna & 2 DIN radio with Carplay	S	S	S	S	S	S	S	S	S
Manual air conditioning	S	S	S	S	S	S	S	S	S
Driver and Passenger airbag	S	S	S	S	S	S	S	S	S
Cruise Control with speed limiter	S	S	S	S	S	S	S	S	S
Swivelling driver' and passenger's seat	S	S	S	S	S	S	S	S	S
Beds with staves	S	S	S	S	S	S	S	S	S

The mass of the approved vehicle includes: driver (75 Kg), diesel tank filled to 100% (60 liters), fresh water filled to 20 liters. (use of the special exhaust valve) and aluminum gas cylinders (max. 15 kg.) full to 90% of their capacity, and tolerance foreseen in the approval phase (+/- 5%) (2007/46 / EC). Anything not included in the standard version of the vehicle, both airframe and chassis, leads to an increase in the curb weight with the consequent reduction of the payload up to the possible reduction of homologated seats in case the total weight is the value of the available payload. The available payloads result from the difference between the maximum permissible mass and the mass in running order and have a tolerance of 5%. During the purchase phase, it is necessary to check the weight of the options to be installed on the vehicle.

S= standard O=optional - = unavailable

VTR= Fiberglass